LEXUS (USA / CAN) RC XC10 RC 350 2WD (USA) (2014-2017)



ENGINE 2GR-FSE Capacity: 7,2 liter (Dry fill), Capacity: 6,2 liter (Service fill), Filter capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 10000 miles/ 12 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 5000 miles/ 6 months		
DIFFERENTIAL REAR Capacity: 1,35 liter		

SP Gear 1071

Check every 15000 miles/ 18 months

CLIMATE

Moderate

DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,35 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

Check every 15000 miles/ 18 months, change every 60000 miles/ 72 months

TRANSMISSION AUTOMATIC AA81E 8/ Capacity: 9,5 liter (Dry fill), Capacity: 3,2 li	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Check every 30000 miles/ 36 months	

Normal

PRODUCT RECOMMENDATION 1

PRODUCT RECOMMENDATION

LEXUS (USA / CAN) RC XC10 RC 350 2WD (USA) (2014-2017)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
01 1 15000 11 / 10 11 1	20000 11 / 20 11	

Check every 15000 miles/18 months, change every 30000 miles/36 months

COOLING SYSTEM Capacity: 9,6-9,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Chook avany 15000 miles/19 menths of	anga ayan, E0000 milaa/60 mantha	

Check every 15000 miles/ 18 months, change every 50000 miles/ 60 months

USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Check every 15000 miles/ 18 months, change every 100000 miles/ 120 months

AIRCONDITIONING R-134a

Capacity: 520-620 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR R-134a

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.