# **LEXUS (EU) IS XE30 IS 250 USE30** (2013-2015)



JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 month	s	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30
Change every 15000 km/ 12 month	s	
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 7500 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30
Change every 7500 km/ 6 months	'	'
DIFFERENTIAL REAR		
Capacity: 1,1-1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071	I	1

Change every 30000 km/48 months

## **LEXUS (EU) IS XE30 IS 250 USE30** (2013-2015)



TRANSMISSION AUTOMATIC A960E 6/1 Capacity: 7,5 liter (Dry fill), Capacity: 1,4 liter (Service fill), Capacity: 4 liter (Torque converter), Capacity: 2,5 liter (Transmission valve body)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 48 months/ 60000 km				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 45000 km/ 36 months, chang	e every 90000 km/ 72 months			
HYDRAULIC BRAKE SYSTEM ABS				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid DOT 3				
Change every 30000 km/ 24 months				

COOLING SYSTEM Capacity: 10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 30000 km, change every 90	000 km	

USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Check every 30000 km, change every 150000 km

### **AIRCONDITIONING** R-134a Capacity: 520-620 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

PRODUCT RECOMMENDATION

### **LEXUS (EU) IS XE30 IS 250 USE30** (2013-2015)



#### AIRCONDITIONING COMPRESSOR

Capacity: 100 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.