# **LEXUS (EU) IS XE30 IS 300H AVE30** (2013-2019)



<b>ENGINE</b> 2AR-FSE Capacity: 5,9 liter (Dry fill), Capacity: 4,5	liter (Service fill), Filter capacity: 0,4 lit	er	
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Bi-Turbo 20W-50			
Change every 15000 km/ 12 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30	
Change every 15000 km/ 12 months			
USE		CLIMATE	
Severe		Mediterranean	
PRODUCT RECOMMENDATION 1			
Bi-Turbo 20W-50			
Change every 7500 km/ 6 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30	
Change every 7500 km/ 6 months			
DIFFERENTIAL REAR Capacity: 1,3-1,4 liter			

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

Change every 30000 km/ 48 months

## **LEXUS (EU) IS XE30 IS 300H AVE30** (2013-2019)



TRANSAXLE ECVT L210 2/1 Capacity: 3,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 48 months/ 60000 km			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Charle avery 45000 km/ 26 months, change avery 00000 km/ 72 months			

Check every 45000 km/ 36 months, change every 90000 km/ 72 months

HYDRAULIC BRAKE SYSTEM			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Change every 30000 km/ 24 months	·		

COOLING SYSTEM Capacity: 8,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 30000 km, change every 90000 km		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 30000 km, change every 150000 km

### LEXUS (EU) IS XE30 IS 300H AVE30 (2013-2019)



COOLING SYSTEM INVERTER Capacity: 2-2,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Check every 30000 km, change every 90000 km			
USE		CLIMATE	
First change only		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant SP 14+			
Check every 30000 km, change every 240000 km			

#### AIRCONDITIONING R-134a

Capacity: 520-620 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

### AIRCONDITIONING COMPRESSOR

Capacity: 120-135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

#### AIRCONDITIONING SYSTEM R-1234yf Capacity: 470-530 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.