LEXUS (EU) RC XC10 RC 350 (2014-2015)



ENGINE 2GR-FSE	u 6 2 litar / Camina fill) Filtar canacitu 0 2 li	
Capacity: 7,2 liter (Dry fill), Capacity use	r: 6,2 liter (Service fill), Filter capacity: 0,3 lit	er CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 15000 km/ 12 month	s	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 0W-20	Duranza ECO 5W-20	Presteza MSP 5W-30
Change every 15000 km/ 12 month	S	
USE		CLIMATE
Severe		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 7500 km/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1 Presteza MSP 0W-20	PRODUCT RECOMMENDATION 2 Duranza ECO 5W-20	Product recommendation 3 Presteza MSP 5W-30
	Duranza LCO 3VV-20	r resteza wor 5vv-50
Change every 7500 km/ 6 months		
DIFFERENTIAL REAR		
Capacity: 1,3-1,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		
Change every 30000 km/ 48 month	s	

LEXUS (EU) RC XC10 RC 350 (2014-2015)



TRANSMISSION AUTOMATIC AA81E 8/1 Capacity: 9,5 liter (Dry fill), Capacity: 3,2 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 48 months/ 60000 km			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 45000 km/ 36 months, change every 90000 km/ 72 months			

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 30000 km/ 24 months	·

COOLING SYSTEM Capacity: 9,7-10 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Change every 30000 km/ 24 months	

AIRCONDITIONING R-134a Capacity: 520-620 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR R-134a

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.