

**LEXUS (EU) RX L1 RX 450H 2WD (2009-2012)****ENGINE 2GR-FXE**

Capacity: 6,1 liter, Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 0W-20</b>	<b>Duranza ECO 5W-20</b>	<b>Presteza MSP 5W-30</b>

*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 0W-20</b>	<b>Duranza ECO 5W-20</b>	<b>Presteza MSP 5W-30</b>

*Change every 7500 km/ 6 months***TRANSAXLE HYBRID SYSTEM P313 1/1**

Capacity: 4,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 60000 km/ 36 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 45000 km/ 36 months, change every 90000 km/ 72 months***HYDRAULIC BRAKE SYSTEM ABS**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 30000 km/ 24 months*

**LEXUS (EU) RX L1 RX 450H 2WD (2009-2012)****COOLING SYSTEM**

Capacity: 11,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Check every 30000 km, change every 90000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Check every 30000 km, change every 150000 km***COOLING SYSTEM INVERTER**

Capacity: 1,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Check every 30000 km, change every 90000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 14+***Check every 30000 km, change every 240000 km***AIRCONDITIONING**

Capacity: 550-650 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING COMPRESSOR**

Capacity: 120-135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*