

LEXUS (EU) RX XU30 RX 300 (2004-2006)**ENGINE 1MZ-FE**

Capacity: 5,5 liter (Dry fill), Capacity: 4,7 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40*Change every 15000 km/ 12 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50*Change every 7500 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Bi-Turbo 15W-40*Change every 7500 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 30000 km/ 48 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube RPC 75W-80

PRODUCT RECOMMENDATION 3

SP Gear 1071*Change every 30000 km/ 48 months*

LEXUS (EU) RX XU30 RX 300 (2004-2006)

TRANSAXLE AUTOMATIC U151F 5/1
Capacity: 9,1 liter (Dry fill), Capacity: 3,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 45000 km/ 36 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Check every 45000 km/ 36 months, change every 90000 km/ 72 months

TRANSFERBOX AUTOMATIC 10365
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Change every 30000 km/ 48 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube RPC 75W-80	SP Gear 1071

Change every 30000 km/ 48 months

HYDRAULIC BRAKE SYSTEM ABS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 30000 km/ 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

Check every 24 months/ 30000 km

LEXUS (EU) RX XU30 RX 300 (2004-2006)**COOLING SYSTEM**

Capacity: 9,4-9,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 30000 km, change every 90000 km

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Check every 30000 km, change every 150000 km

AIRCONDITIONING R-134a

Capacity: 600-650 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING COMPRESSOR R-134a

Capacity: 135 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.