LINCOLN AVIATOR AVIATOR 4.6 V8 32V AWD (2002-2005)



ENGINE Capacity: 5,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Check every 1 months, change every 5000 miles/ 6 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Duranza ECO 5W-20		
Change every 3000 miles/ 3 months/ 200 hours		

DIFFERENTIAL FRONT (4x4) Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
Change every 150000 miles	

Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 100000 miles	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 50000 miles	

DIFFERENTIAL REAR

Change every 60000 miles

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

LINCOLN AVIATOR AVIATOR 4.6 V8 32V AWD (2002-2005)



TRANSAXLE AUTOMATIC Capacity: 12 liter (Dry fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Change every 30000 miles	

TRANSFERBOX (4x4) Capacity: 1,25-1,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Change every 150000 miles		·
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 15000 miles, change every 24 months		
USE		CLIMATE
Severe		Moderate

Check every 5000 miles, change every 24 months

POWER STEERING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	ATF Dexron II-D
Check every 6 months		

LINCOLN AVIATOR AVIATOR 4.6 V8 32V AWD (2002-2005)



COOLING SYSTEM Capacity: 19 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	
Check every 15000 miles, change every 50000 miles/ 36 months		
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 11	
Check every 15000 miles, change every 100000 miles/ 60 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.