

LINCOLN MKS MKS 3.5 V6 ECOBOOST

(2008-2011)

**ENGINE EcoBoost**

Capacity: 5,2 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Presteza MSP 5W-30	Avanza MSP+ 5W-30	Avanza RPC 5W-30

*Change every 10000 miles/ 12 months***DIFFERENTIAL REAR**

Capacity: 1,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

*Change every 150000 miles***TRANSAXLE AUTOMATIC 6F50 6/1**

Capacity: 10,3 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

*Change every 150000 miles***TRANSAXLE AUTOMATIC 6F55 6/1**

Capacity: 11 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		

*Change every 150000 miles***TRANSFERBOX**

Filter capacity: 0,53 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

LINCOLN MKS MKS 3.5 V6 ECOBOOST

(2008-2011)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 15000 miles, change every 24 months

COOLING SYSTEM

Capacity: 10,8 liter

USE		CLIMATE
Normal, green fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 50000 miles/ 36 months

USE		CLIMATE
First change only, green fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 100000 miles/ 72 months

USE		CLIMATE
First change only, orange fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 100000 miles/ 72 months

USE		CLIMATE
Normal, orange fluid		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 50000 miles/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.