## **MASERATI BITURBO BITURBO 430** (1988-1991)



<b>ENGINE</b> AM 473 Capacity: 5,5 liter, Filter capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Emperol 10W-40	
Change every 7500 km	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Emperol 10W-40	
Change every 5000 km	

DIFFERENTIAL REAR Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
Check every 7500 km, change every 450	00 km/ 24 months

TRANSMISSION AUTOMATIC ZF 3/1
Capacity: 5,5 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2
ATF Dexron II-D ATF-A

Change every 45000 km/24 months

TRANSMISSION MANUAL 5/1 Capacity: 1,7 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Gearlube GL-4 80W-90		
Check every 7500 km, change every 22500 km/ 12 months		

## **MASERATI BITURBO BITURBO 430** (1988-1991)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 45000 km/24 months		

POWER STEERING Capacity: 0,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
ATF Dexron II-D	ATF-A		

GREASE POINTS/NIPPLES WHEEL BEARINGS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Labora Grease	Multi Purpose Grease 3		
Change every 22500 km/ 12 month	78		

COOLING SYSTEM Capacity: 8,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		
Change every 22500 km/ 12 months	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.