

MAYBACH MAYBACH 62 (S) W240

MAYBACH 62 S 240.177/179 (2006-2013)



ENGINE 285.980
Capacity: 10,5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar 0W-40		

DIFFERENTIAL REAR
Capacity: 1,6-1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

Change every 40000 km

TRANSMISSION AUTOMATIC 722.649 5/1
Capacity: 8 liter (Dry fill), Capacity: 6,5 liter (Service fill)

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 km

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

HYDRAULIC BRAKE SYSTEM
Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 24 months

MAYBACH MAYBACH 62 (S) W240

MAYBACH 62 S 240.177/.179 (2006-2013)

**POWER STEERING**

Capacity: 1,3-1,5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 36 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

*Change every 250000 km/ 180 months***AIRCONDITIONING COMPRESSOR**

Capacity: 120 CM3 (Compressor 6SEU14C), Capacity: 170 CM3 (Compressor 7SEU17C)

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 950 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.