

MAZDA (EU) 2 DY 2 1.25 16V (2002-2007)



MOTOR MZI 1.25
Kapacitet: 3,8 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40

Skift alle 10000 km

TRANSAKSEL MANUEL 5/1
Kapacitet: 2,3 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 20000 km/ 12 måneder

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 20000 km, skift alle 40000 km/ 24 måneder

SERVOSTYRING

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2032		

Kontroller alle 20000 km/ 12 måneder

MAZDA (EU) 2 DY 2 1.25 16V (2002-2007)



KØLESYSTEM

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 40000 km/ 24 måneder, skift alle 120 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.