

MAZDA (EU) 5 CR 5 2.0 CITD HP DPF (2005-2008)



MOTOR RF

Kapacitet: 4,1 liter (Servicepåfyldning), Filterkapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Elvado LSP 5W-30

Skift alle 20000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Elvado LSP 5W-30

Kontroller alle 3000 km, skift alle 10000 km/ 12 måneder

TRANSAKSEL AUTOMATISK 4/1

Kapacitet: 7,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 12 måneder

TRANSAKSEL MANUEL A26M-R 6/1

Kapacitet: 2,55 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Skift alle 100000 km/ 60 måneder

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

PRODUKTANBEFALING 3

Drauliquid DOT 3

Skift alle 40000 km/ 48 måneder

MAZDA (EU) 5 CR 5 2.0 CITD HP DPF (2005-2008)



SERVOSTYRING

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

PRODUKTANBEFALING 2
ATF Dexron II-D

Kontroller alle 12 måneder

KØLESYSTEM

Kapacitet: 8 liter, Kapacitet: 8,5 liter (med 4-zoners airconditionssystem)

ANVEND
Forlænget

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 15+

PRODUKTANBEFALING 2
Coolant SP 12

PRODUKTANBEFALING 3
Coolant -38 Organic NF

Kontroller alle 40000 km/ 24 måneder, skift alle 200000 km/ 132 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.