

MAZDA (EU) MPV LW MPV 2.0 16V (1999-2002)



MOTOR FS

Kapacitet: 3,5 liter, Filterkapacitet: 0,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Skift alle 15000 km/ 12 måneder

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

Asyntho 5W-30

PRODUKTANBEFALING 2

Emperol 10W-40

Skift alle 10000 km

TRANSAKSEL AUTOMATISK 4/1

Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2032

PRODUKTANBEFALING 2

ATF Dexron II-D

Kontroller alle 24 måneder/ 30000 km

TRANSAKSEL MANUEL 5/1

Kapacitet: 2,7 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-4 80W-90

PRODUKTANBEFALING 2

Gearlube GL-5 80W-90

Skift alle 90000 km/ 72 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Syngear 75W-90

Skift alle 90000 km/ 72 måneder

MAZDA (EU) MPV LW MPV 2.0 16V (1999-2002)



HYDRAULISK BREMSESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

PRODUKTANBEFALING 3
Drauliquid DOT 3

Skift alle 30000 km/ 24 måneder

HYDRAULISK KOBLINGSSYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

PRODUKTANBEFALING 3
Drauliquid DOT 3

Kontroller alle 15000 km/ 12 måneder

SERVOSTYRING

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Matic 2032

PRODUKTANBEFALING 2
ATF Dexron II-D

Kontroller alle 15000 km/ 12 måneder

KØLESYSTEM

Kapacitet: 11,2 liter, Kapacitet: 12 liter (+ bageste varmer)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant -38 Organic NF

Skift alle 90000 km/ 48 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.