## MAZDA (EU) 3 BL 3 1.6 CITD (80 KW) DPF (2009-2010)



ENGINE MZ-CD 1.6 Capacity: 3,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Duranza LSP 5W-30	Asyntho 5W-30	Emperol 10W-40		

Change every 20000 km/ 12 months

TRANSAXLE MANUAL J65M-R 5/1 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		
Check every 20000 km/ 12 months		

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 40000 km/ 48 months

POWER STEERING ELECTRONIC/HYDRAULIC Capacity: 1 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Matic 2032	ATF Dexron II-D			

Check every 20000 km/ 12 months

COOLING SYSTEM Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 40000 km/ 24 months, change every 200000 km/ 132 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

## MAZDA (EU) 3 BL 3 1.6 CITD (80 KW) DPF (2009-2010)



information contained herein is subject to changes without notification.