

**MAZDA (EU) 323F 323F 1.5I 16V (1995-1998)****ENGINE**

Capacity: 3,5 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Asyntho 5W-30***Change every 15000 km/ 12 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 4,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Dexron II-D****TRANSAXLE MANUAL 5/1**

Capacity: 2,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

PRODUCT RECOMMENDATION 3

**Syngear 75W-90***Check every 30000 km/ 24 months, change every 90000 km/ 72 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 24 months***POWER STEERING**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 2032**

PRODUCT RECOMMENDATION 2

**ATF Dexron II-D***Check every 15000 km/ 12 months*

**MAZDA (EU) 323F 323F 1.5I 16V (1995-1998)****COOLING SYSTEM**

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF***Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*