PRODUCT RECOMMENDATION

# MAZDA (EU) 6 GG/GY 6 1.8 (2002-2007)

## ENGINE L-8

Capacity: 4,6 liter (Dry fill), Capacity: 4,3 liter (Service fill), Filter capacity: 0,4 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Duranza LSP 5W-30** | **Asyntho 5W-30** | **Emperol 10W-40** |

*Change every 20000 km/ 12 months*

| USE | CLIMATE |
|---|---|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Duranza LSP 5W-30** | **Asyntho 5W-30** | **Emperol 10W-40** |

*Change every 10000 km/ 12 months*

## TRANSAXLE MANUAL G35M-R 5/1

Capacity: 2,87 liter

| USE | CLIMATE |
|---|---|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |
|---|---|
| **Gearlube GL-4 80W-90** | **Gearlube GL-5 80W-90** |

*Change every 100000 km/ 60 months*

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **SP Gear 1011** | **Syngear TDL 75W-90** | **Syngear 75W-90** |

*Change every 100000 km/ 60 months*

## HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | **Drauliquid DOT 3** |

*Check every 20000 km, change every 40000 km/ 24 months*

| USE | CLIMATE |
|---|---|
| Severe | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | **Drauliquid DOT 3** |

*Check every 20000 km, change every 12 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# MAZDA (EU) 6 GG/GY 6 1.8 (2002-2007)

## POWER STEERING
Capacity: 0,8 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **SP Matic 2032** | | |

*Check every 20000 km/ 12 months*

## COOLING SYSTEM
Capacity: 7,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Coolant -38 Organic NF** | | |

*Check every 20000 km, change every 24 months*

| USE | | CLIMATE |
|---|---|---|
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Coolant -38 Organic NF** | | |

*Check every 30000 km/ 24 months, change every 90000 km/ 48 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367