MAZDA (EU) 6 GH/GZ 6 2.2 CITD (95 KW)

(2009-2010)



ENGINE MZR-CD 2.2 Capacity: 5,7 liter (Dry fill), Capacity: 4,7 liter (Service fill)				
use Normal	climate Moderate			
PRODUCT RECOMMENDATION 1 Elvado LSP 5W-30				

Change every 20000 km/ 12 months

TRANSAXLE MANUAL A26M-R 6/1 Capacity: 2,4-2,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
01 4000001 /00 #	<u> </u>	

Change every 100000 km/60 months

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	
Change every 40000 km/ 48 months	-	ı ·	

COOLING SYSTEM Capacity: 9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

Check every 40000 km/24 months, change every 200000 km/132 months

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM Capacity: 500-550 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.