## MAZDA (EU) 6 GH/GZ 6 2.5 S-VT (2009-2010)



ENGINE MZR 2.5 Capacity: 5,5 liter (Dry fill), Capacity: 5 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Duranza ECO 5W-20	Presteza MSP 5W-30	Duranza LSP 5W-30		

Change every 20000 km/ 12 months

TRANSAXLE AUTOMATIC FS5A-EL 5/1 Capacity: 8,14 liter (Dry fill), Capacity: 3 liter (Service fill)				
USE	CLIMATE			
Normal	Modera	te		
PRODUCT RECOMMENDATION 1				
SP Matic 4026				
Check every 40000 km/ 24 months				

TRANSAXLE MANUAL G66M-R 6/1 Capacity: 2,85 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	
Change over 100000 km/ 10 months	·

Change every 100000 km/48 months

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3
Change even 10000 km/ 19 menths		

Change every 40000 km/ 48 months

COOLING SYSTEM Capacity: 7,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
Check every 40000 km/ 24 months, change every 200000 km/ 132 months		

## MAZDA (EU) 6 GH/GZ 6 2.5 S-VT (2009-2010)



## **AIRCONDITIONING COMPRESSOR**

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## **AIRCONDITIONING SYSTEM**

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.