

# MAZDA (EU) 6 GJ/GL 6 SKYACTIV-G 2.0 (107 KW) (2012-2017)

**ENGINE SKYACTIV-G 2.0**

Capacity: 4,9 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 0W-20</b>	<b>Helar SP LL-03 5W-30</b>	<b>Presteza MSP 5W-30</b>

*Change every 10000 km/ 6 months*

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Presteza MSP 0W-20</b>	<b>Helar SP LL-03 5W-30</b>	<b>Presteza MSP 5W-30</b>

*Change every 20000 km/ 12 months***TRANSAXLE MANUAL C66M-R 6/1**

Capacity: 1,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Gear 5015</b>		

*Change every 180000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 40000 km/ 24 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

*Change every 20000 km/ 12 months*

# MAZDA (EU) 6 GJ/GL 6 SKYACTIV-G 2.0 (107 KW) (2012-2017)

**COOLING SYSTEM**

Capacity: 6,5-6,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

Check every 40000 km/ 24 months, change every 100000 km/ 60 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 14+</b>		

Check every 40000 km/ 24 months, change every 200000 km/ 120 months

**AIRCONDITIONING COMPRESSOR**

Capacity: 100 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM R-1234yf**

Capacity: 475-525 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM R-134a**

Capacity: 465-515 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*