

**MAZDA (EU) 626 626 1.6 (1984-1986)****ENGINE F6**

Capacity: 3,9 liter, Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 15W-40**

## PRODUCT RECOMMENDATION 2

**HDX 20W-50***Change every 7500 km/ 6 months*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Emperol 10W-40***Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 6,2 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**ATF-F (Ford)****TRANSAXLE MANUAL 5/1**

Capacity: 3,4 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gearlube GL-4 80W-90**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-5 80W-90***Check every 15000 km/ 12 months, change every 45000 km/ 36 months***HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

## PRODUCT RECOMMENDATION 3

**Drauliquid DOT 3***Change every 45000 km/ 36 months*

**MAZDA (EU) 626 626 1.6 (1984-1986)****POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF-F (Ford)</b>		

**GREASE POINTS/NIPPLES WHEEL BEARINGS**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 45000 km/ 36 months*

**COOLING SYSTEM**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Change every 30000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*