## MAZDA (EU) CX-5 KE CX-5 SKYACTIV-D 2.2 (110 KW) 2WD (2012-2017)



<b>ENGINE</b> SKYACTIV-D 2.2 Capacity: 6 liter (Dry fill), Capacity: 5,1 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30		
Change every 20000 km/ 12 months				
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30		
Change every 10000 km/ 6 months				

TRANSAXLE AUTOMATIC GW6A-EL 6/1 Capacity: 7,8 liter (Dry fill), Capacity: 3,5-4,9 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Check every 20000 km/ 12 months	'			

TRANSAXLE MANUAL D66M-R 6/1 Capacity: 2,4 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
Change every 180000 km		

## MAZDA (EU) CX-5 KE CX-5 SKYACTIV-D 2.2 (110 KW) 2WD (2012-2017)



**Drauliquid DOT 3** 

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3	
Change every 40000 km/ 24 months			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	

**Drauliquid-S DOT 4** 

Change every 20000 km/ 12 months

Drauliquid-LV Super DOT 4

CLIMATE
Madausta
Moderate

Check every 40000 km/24 months, change every 100000 km/60 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 40000 km/24 months, change every 200000 km/120 months

## AIRCONDITIONING COMPRESSOR

Capacity: 100 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 445-495 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.