

MERCEDES-BENZ (EU) CLC-KLASSE CL203

CLC 350 203.756 (2008-2010)



MOTOR M272.960
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Emperol 5W-50

Skift alle 20000 km

DIFFERENTIALE BAG
Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

GEAR AUTOMATISK 722.9XX FRA OG MED PRODUKTIONSNR. 2834527 722.9xx 7/1
Kapacitet: 9 liter (Tør efterfyld)

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 2094

Skift alle 60000 km

GEAR AUTOMATISK 722.9XX OP TIL PRODUKTIONSNR. 2834526 722.9xx 7/1
Kapacitet: 9 liter (Tør efterfyld)

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 60000 km

GEAR MANUEL 716.6xx 6/1
Kapacitet: 1,2 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 5015

MERCEDES-BENZ (EU) CLC-KLASSE CL203

CLC 350 203.756 (2008-2010)



HYDRAULISK AKTIVERING GEARCASSE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

PRODUKTANBEFALING 2

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.