

MERCEDES-BENZ (EU) CLS-KLASSE C218 / X218 CLS 350 CDI 4MATIC BLUEEFFICIENCY DPF 218.393/993 (2013-



MOTOR OM642.854, OM642.858
Kapacitet: 8 liter

ANVEND	KLIMA
Fleksibel (max)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

Skift alle 25000 km

DIFFERENTIALE BAG
Kapacitet: 1,1-1,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1071		

DIFFERENTIALE FOR
Kapacitet: 0,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1071		

GEAR AUTOMATISK 722.96x 7/1
Kapacitet: 9,7 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2094		

Skift alle 125000 km/ 60 måneder

HYDRAULISK BREMSESYSYSTEM ABS
Kapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid-S DOT 4		

Skift alle 24 måneder

MERCEDES-BENZ (EU) CLS-KLASSE C218 / X218 CLS 350 CDI 4MATIC BLUEEFFICIENCY DPF 218.393/993 (2013-



KOELSYSTEM

Kapacitet: 10,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

PRODUKTANBEFALING 2

Coolant SP 12 EVO

Skift alle 250000 km/ 180 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 120 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM

Kapacitet: 590 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.