

MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 300 4MATIC 212.080/280 (2013-2016)



ENGINE M276.952
Capacity: 6,5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar 0W-40		

DIFFERENTIAL FRONT
Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

DIFFERENTIAL REAR 187 FE, Ø 187 mm
Capacity: 0,95 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR 200 FE, Ø 200 mm
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR 215 FE, Ø 215 mm
Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 300 4MATIC 212.080/280 (2013-2016)



TRANSMISSION AUTOMATIC 722.96x 7/1
Capacity: 9,7 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2094		

Change every 125000 km/ 60 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2094		

Change every 50000 km/ 36 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 24 months

COOLING SYSTEM
Capacity: 9,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR
Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM
Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.