

MERCEDES-BENZ (EU) GL-KLASSE X164

GL 420 CDI DPF 4MATIC 164.828 (2007-2009)



MOTOR OM629.91x
Kapacitet: 11,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

Skift alle 25000 km/ 12 måneder

DIFFERENTIALE BAG
Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

DIFFERENTIALE BAG DIFFERENTIALESPÆR
Kapacitet: 1,6 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1071

DIFFERENTIALE FOR
Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

GEAR AUTOMATISK 722.9xx 7/1
Kapacitet: 9 liter

ANVEND
Første skift kun

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 60000 km

MERCEDES-BENZ (EU) GL-KLASSE X164

GL 420 CDI DPF 4MATIC 164.828 (2007-2009)

**REDUKTIONSGEARKASSE**

Kapacitet: 0,5 liter, Kapacitet: 1,5 liter (+ dobbelt område)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 4026		

HYDRAULISK BREMSESYSTEM ABS

Kapacitet: 0,8 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid-S DOT 4		

Skift alle 24 måneder

SERVOSTYRING

Kapacitet: 1,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 4026	SP Matic 2032	

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 11	Coolant SP 12 EVO	

Skift alle 250000 km/ 180 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.