

MERCEDES-BENZ (EU) GLK-KLASSE X204

GLK 280 4MATIC 204.981 (2008-2009)



MOTOR M272.948
Kapacitet: 7 liter

ANVEND		KLIMA
Flexibel (max)		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar 0W-40	Emperol 5W-40	Emperol 5W-50

DIFFERENTIALE BAG
Kapacitet: 1-1,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1071	Gearlube LS 80W-90	

DIFFERENTIALE FOR
Kapacitet: 0,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1071	Gearlube LS 80W-90	

GEAR AUTOMATISK 722.9xx 7/1
Kapacitet: 9,7 liter (Tør efterfyld)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 4026		

ANVEND		KLIMA
Første Service		Moderat
PRODUKTANBEFALING 1		
SP Matic 4026		

Skift alle 50000 km/ 36 måneder

MERCEDES-BENZ (EU) GLK-KLASSE X204

GLK 280 4MATIC 204.981 (2008-2009)



HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KØLESYSTEM

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

PRODUKTANBEFALING 2

Coolant SP 12 EVO

Skift alle 250000 km/ 180 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 120 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM

Kapacitet: 590 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.