

MERCEDES-BENZ (EU) GLK-KLASSE X204

GLK 320 CDI 4MATIC 204.983 (2008-2009)



MOTOR OM642.961

Kapacitet: 8 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

DIFFERENTIALE BAG

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

DIFFERENTIALE FOR

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

GEAR AUTOMATISK 722.9xx 7/1

Kapacitet: 9,7 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 50000 km/ 36 måneder

MERCEDES-BENZ (EU) GLK-KLASSE X204

GLK 320 CDI 4MATIC 204.983 (2008-2009)



HYDRAULISK BREMSESYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Fluid 3013

KØLESYSTEM

Kapacitet: 5,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Coolant SP 11

PRODUKTANBEFALING 2
Coolant SP 12 EVO

Skift alle 250000 km/ 180 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 120 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM

Kapacitet: 590 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.