

MERCEDES-BENZ (EU) M-KLASSE W164

ML 280 CDI 4MATIC 164.120 (2007-2009)



MOTOR OM642.940

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

Skift alle 25000 km/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

DIFFERENTIALE BAG DIFFERENTIALESPÆR

Kapacitet: 1,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

DIFFERENTIALE FOR

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

GEAR AUTOMATISK 722.9xx 7/1

Kapacitet: 9 liter

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 60000 km

MERCEDES-BENZ (EU) M-KLASSE W164

ML 280 CDI 4MATIC 164.120 (2007-2009)



REDUKTIONSGEARKASSE

Kapacitet: 0,5 liter, Kapacitet: 1,5 liter (+ dobbelt område)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

HYDRAULISK BREMSESYSTEM ABS

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING

Kapacitet: 1,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

PRODUKTANBEFALING 2

SP Matic 2032

KØLESYSTEM

Kapacitet: 6,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

PRODUKTANBEFALING 2

Coolant SP 12 EVO

Skift alle 250000 km/ 180 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.