

MERCEDES-BENZ (EU) S-KLASSE W222 / V222 / X222 S 500 E PLUG-IN HYBRID 222.163 (2014-2018)



MOTOR M276.824
Kapacitet: 6,5 liter

ANVEND	KLIMA
Fleksibel (max)	Moderat

PRODUKTANBEFALING 1		
Helar 0W-40		

Skift alle 25000 km

DIFFERENTIALE BAG 200 FE, Ø 200 mm
Kapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1071		

DIFFERENTIALE BAG 215 FE, Ø 215 mm
Kapacitet: 1,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1071		

DIFFERENTIALE BAG 240 FE, Ø 240 mm
Kapacitet: 1,6 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Gear 1071		

GEAR AUTOMATISK 724.204 7/1
Kapacitet: 9 liter (Tør efterfyld)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2094		

Skift alle 125000 km/ 60 måneder

MERCEDES-BENZ (EU) S-KLASSE W222 / V222 / X222 S 500 E PLUG-IN HYBRID 222.163 (2014-2018)



ACTIVE BODY CONTROL SYSTEMET

Kapacitet: 4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

HYDRAULISK BREMSESYSTEM ABS

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 12,3 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Skift alle 200000 km/ 120 måneder

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 110 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

KLIMAANLÆGSSYSTEM

Kapacitet: 660 gram, Kapacitet: 770 gram (+ kode 582)

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.