

MERCEDES-BENZ (EU) SL-KLASSE R230

SL 63 AMG 230.470 (2008-2012)



MOTOR M156.981
Kapacitet: 8 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar 0W-40

DIFFERENTIALE BAG Ø 215 mm
Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

Skift alle 60000 km

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Gearlube Racing 75W-140

Skift alle 3000 km

GEAR AUTOMATISK 722.9XX FRA OG MED PRODUKTIONSNR. 2834527 722.9xx 7/1
Kapacitet: 7,1 liter (Tør efterfyld)

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2094

Skift alle 60000 km

GEAR AUTOMATISK 722.9XX OP TIL PRODUKTIONSNR. 2834526 722.9xx 7/1
Kapacitet: 7,1 liter (Tør efterfyld)

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 60000 km

MERCEDES-BENZ (EU) SL-KLASSE R230

SL 63 AMG 230.470 (2008-2012)



ACTIVE BODY CONTROL SYSTEMET

Kapacitet: 4 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

HYDRAULIKSYSTEM KALECHE

Kapacitet: 0,13-0,18 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3023		

HYDRAULISK BREMSESYSTEM ABS

Kapacitet: 1,4-2,25 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid-S DOT 4		

Skift alle 24 måneder

SERVOSTYRING

Kapacitet: 1-1,25 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 11	Coolant SP 12 EVO	

Skift alle 250000 km/ 180 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.