

MERCEDES-BENZ (EU) SLK-KLASSE R171

SLK 200 KOMPRESSOR 171.445 (2008-2011)



MOTOR M271.954
Kapacitet: 5,5 liter

ANVEND

Forlænget

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar 0W-40

Skift alle 25000 km/ 12 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Emperol 5W-50

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Gearlube LS 80W-90

GEAR AUTOMATISK 722.6xx 5/1

Kapacitet: 8 liter

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Skift alle 60000 km

GEAR MANUEL 716.6xx 6/1

Kapacitet: 1,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

MERCEDES-BENZ (EU) SLK-KLASSE R171

SLK 200 KOMPRESSOR 171.445 (2008-2011)



HYDRAULISYSTEEM KALECHE

Kapaciteit: 0,42 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3023

HYDRAULISK AKTIVERING GEARKASSE

Kapaciteit: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

HYDRAULISK BREMSE- & KOBLINGSSYSTEEM

Kapaciteit: 0,45-0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING

Kapaciteit: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KØLESYSTEEM

Kapaciteit: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

PRODUKTANBEFALING 2

Coolant SP 12 EVO

Skift alle 250000 km/ 180 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.