

MERCEDES-BENZ (EU) A-CLASS W169 / C169 A 160 CDI DPF 169.006 / 169.306 (2004- 2007)



ENGINE OM640.942
Capacity: 5,8 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.

TRANSAXLE AUTOMATIC 722.8x (CVT) 1/1
Capacity: 4 liter, Capacity: 6 liter (+ torque converter), Capacity: 5,7-6,5 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4016		

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.

TRANSAXLE MANUAL 716.5xx 5/1
Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 5015		

This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.

HYDRAULIC BRAKE/CLUTCH SYSTEM
Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

*This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.
Change every 24 months*

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) A-CLASS W169 / C169 A 160 CDI DPF 169.006 / 169.306 (2004- 2007)



COOLING SYSTEM

Capacity: 9,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

*This vehicle is equipped with ASSYST or ASSYST Plus. ASSYST indicates when the vehicle needs Service.
Change every 250000 km/ 180 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.