MERCEDES-BENZ (EU) C-CLASS W204 / S204 / C204 C 200 CDI DPF 204.001/201



(2009-2014)

use Flexible (max)	
Helar SP LL-03 5W-30	Presteza MSP 5W-30

Change every 25000 km

DIFFERENTIAL REAR 187 FE, Ø 187 Capacity: 0,95 liter	mm	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

DIFFERENTIAL REAR 215 FE, Ø 215 mm Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

CLIMATE
Moderate

MERCEDES-BENZ (EU) C-CLASS W204 / S204 / C204 C 200 CDI DPF 204.001/201



(2009-2014)

(=======)		
TRANSMISSION AUTOMATIC 722.9xx 7. Capacity: 9 liter (Dry fill)	/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 125000 km/ 60 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 50000 km/ 36 months		
TRANSMISSION MANUAL 711.653 6/1 Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
TRANSMISSION MANUAL 716.6xx 6/1 Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		
HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		
Change every 24 months		

MERCEDES-BENZ (EU) C-CLASS W204 / S204 / C204 C 200 CDI DPF 204.001/201



(2009-2014)

POWER STEERING Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 10 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 11	Coolant SP 12 EVO		
01/100	4		

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.