PRODUCT RECOMMENDATION

## MERCEDES-BENZ (EU) C-CLASS W204 / S204 / C204 C 300 4MATIC 204.080 (2011-



2014)

ENGINE M276.957 Capacity: 6,5 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Helar 0W-40	
Change every 25000 km	

<b>DIFFERENTIAL FRONT</b> Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

DIFFERENTIAL REAR Capacity: 1-1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

TRANSMISSION AUTOMATIC 722.96x 7/1 Capacity: 9,7 liter (Dry fill)	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2094	
Change every 50000 km/ 36 months	·

HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	

PRODUCT RECOMMENDATION

## **MERCEDES-BENZ (EU) C-CLASS W204/** S204 / C204 C 300 4MATIC 204.080 (2011-



2014)

POWER STEERING Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 11	Coolant SP 12 EVO		
01 0500001 //00	4		

Change every 250000 km/ 180 months

## AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.