

MERCEDES-BENZ (EU) C-CLASS W205 / V205 / S205 / C205 / A205 C 200 205.042/142/242/342/442 (2014-2019)



ENGINE M274.920
Capacity: 7 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

Change every 25000 km

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 3

Presteza MSP 5W-30

Change every 15000 km

DIFFERENTIAL REAR ALU-HAG 183
Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

DIFFERENTIAL REAR FE-HAG 187
Capacity: 0,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

DIFFERENTIAL REAR FE-HAG 200
Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

MERCEDES-BENZ (EU) C-CLASS W205 / V205 / S205 / C205 / A205 C 200 205.042/142/242/342/442 (2014-2019)

**DIFFERENTIAL REAR FE-HAG 215**

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR FE-HAG 225

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

TRANSMISSION AUTOMATIC 722.9xx 7/1

Capacity: 9 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		

*Change every 125000 km/ 60 months***TRANSMISSION AUTOMATIC 725.0xx 9/1**

Capacity: 10 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2096		

*Change every 125000 km/ 60 months***TRANSMISSION MANUAL 716.702 6/1**

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) C-CLASS W205 / V205 / S205 / C205 / A205 C 200 205.042/142/242/342/442 (2014-2019)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

Change every 24 months

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

Change every 200000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.