MERCEDES-BENZ (EU) C-CLASS W205 / V205 / S205 / C205 / A205 C 400 4MATIC 205.066/266/344/466 (2014-2018)



ENGINE M276.823 Capacity: 6,5 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Helar 0W-40	

DIFFERENTIAL FRONT Capacity: 0,55 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR ALU-HAG 183 Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

DIFFERENTIAL REAR FE-HAG 187 Capacity: 0,85 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

DIFFERENTIAL REAR FE-HAG 200 Capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

MERCEDES-BENZ (EU) C-CLASS W205 / V205 / S205 / C205 / A205 C 400 4MATIC 205.066/266/344/466 (2014-2018)



DIFFERENTIAL REAR FE-HAG 215 Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

DIFFERENTIAL REAR FE-HAG 225 Capacity: 1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

TRANSFERBOX Capacity: 0,65 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2094	
Change every 125000 km/ 60 months	'

TRANSMISSION AUTOMATIC 722.96x 7/1 Capacity: 9,7 liter (Dry fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2094	
Change every 125000 km/ 60 months	

TRANSMISSION AUTOMATIC 725.0xx 9 Capacity: 10-11 liter (Dry fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2096	
Change every 125000 km	

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) C-CLASS W205 / V205 / S205 / C205 / A205 C 400 4MATIC 205.066/266/344/466 (2014-2018)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		
Change every 24 months		

COOLING SYSTEM Capacity: 0-0 liter (Between min and	d max.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 12++	Coolant SP 12 EVO		
Change aven; 200000 km/ 120 mar	nthe		

Change every 200000 km/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.