

# MERCEDES-BENZ (EU) CLA-CLASS C117 / X117 CLA 200 CDI (OM 651, 1.8) 117.301 (2013-2015)



**ENGINE** OM651.901  
Capacity: 7 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Helar SP LL-03 0W-30</b>	<b>Helar SP LL-03 5W-30</b>	<b>Presteza MSP 5W-30</b>

*Change every 25000 km*

**TRANSAXLE MANUAL** 711.642 6/1  
Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Gear 5015</b>		

**TRANSAXLE SEMI-AUTOMATIC** 724.003 7/1  
Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 2072</b>		

*Change every 100000 km/ 60 months*

**HYDRAULIC BRAKE/CLUTCH SYSTEM**  
Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		

*Change every 24 months*

**COOLING SYSTEM AS OF 04-2014**  
Capacity: 9,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Coolant SP 12 EVO</b>		

*Change every 200000 km/ 120 months*

# MERCEDES-BENZ (EU) CLA-CLASS C117 / X117 CLA 200 CDI (OM 651, 1.8) 117.301 (2013-2015)

**COOLING SYSTEM UP TO 04-2014**

Capacity: 9,6 liter

USE	CLIMATE
Normal	Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 11**

Change every 200000 km/ 120 months

**AIRCONDITIONING COMPRESSOR**

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM**

Capacity: 650 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*