

MERCEDES-BENZ (EU) CLK-CLASS C208 / A208 CLK 320 (1997-2002)



ENGINE M112.940
Capacity: 8 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Emperol 5W-50

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200

DIFFERENTIAL REAR
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200

DIFFERENTIAL REAR LIMITED SLIP
Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200

TRANSMISSION AUTOMATIC 722.6xx 5/1

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200

MERCEDES-BENZ (EU) CLK-CLASS C208 / A208 CLK 320 (1997-2002)



HYDRAULIC LEVELLING SYSTEM

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200
Change every 24 months

POWER STEERING

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200

COOLING SYSTEM

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

Service intervals for vehicles with ASSYST: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 km ago: Service A, >2200
Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.