

MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 250 CDI BLUEEFFICIENCY DPF 218.303/903 (2012-2014)

**ENGINE OM651.924**

Capacity: 6,5 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

*Change every 25000 km***DIFFERENTIAL REAR**

Capacity: 1,1-1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Gear 1071		

TRANSMISSION AUTOMATIC 722.9xx 7/1

Capacity: 9 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2094		

*Change every 125000 km/ 60 months***TRANSMISSION AUTOMATIC 725.011 9/1**

Capacity: 10 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2096		

*Change every 125000 km/ 60 months***HYDRAULIC BRAKE SYSTEM ABS**

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 24 months

MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 250 CDI BLUEEFFICIENCY DPF 218.303/903 (2012-2014)

**COOLING SYSTEM**

Capacity: 10,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.