

MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 350 BLUETEC 218.326 (2013-2015)



ENGINE OM642.852
Capacity: 8 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

Change every 25000 km

DIFFERENTIAL REAR 200 FE, Ø 200 mm
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR 215 FE, Ø 215 mm
Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

TRANSMISSION AUTOMATIC 722.9xx 7/1
Capacity: 9 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		

Change every 125000 km/ 60 months

TRANSMISSION AUTOMATIC 725.011 9/1
Capacity: 10 liter (Dry fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2096		

Change every 125000 km/ 60 months

MERCEDES-BENZ (EU) CLS-CLASS C218 / X218 CLS 350 BLUETEC 218.326 (2013-2015)



HYDRAULIC BRAKE SYSTEM ABS

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 24 months*

COOLING SYSTEM

Capacity: 10,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO*Change every 250000 km/ 180 months*

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.