

MERCEDES-BENZ (EU) E-CLASS W210 / S210 E 250 TURBODIESEL 210.015/215 (1997-1998)



ENGINE OM605LA
Capacity: 6,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Bi-Turbo 20W-50		

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Emperol 10W-40	Bi-Turbo 15W-40

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Change every 15000 km/ 12 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Bi-Turbo 20W-50		

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Change every 7500 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 5W-40	Emperol 10W-40	Bi-Turbo 15W-40

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Change every 7500 km/ 6 months

DIFFERENTIAL REAR
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1071	Gearlube GL-5 80W-90	Gearlube LS 80W-90

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

MERCEDES-BENZ (EU) E-CLASS W210 / S210 E 250 TURBODIESEL 210.015/215 (1997-1998)



DIFFERENTIAL REAR LIMITED SLIP

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

TRANSMISSION MANUAL 717.4XX AS OF PRODUCTION NR. 7 340 241 5/1

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

TRANSMISSION MANUAL 717.4XX UP TO PRODUCTION NR. 7 340 240 5/1

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 4026	SP Matic 2032	ATF-A

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

HYDRAULIC LEVELLING SYSTEM

Capacity: 2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Change every 24 months

MERCEDES-BENZ (EU) E-CLASS W210 / S210 E 250 TURBODIESEL 210.015/215 (1997-1998)



POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Check every 30000 km

COOLING SYSTEM

Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Service intervals for vehicles with ASSYST, from 1.3.1997 onwards: A display indicates when the next service is due. First service for new cars is a Service B. If the last service was a Service A: Service B. If the last service was a Service B: <22000 k Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.