

PRODUCT RECOMMENDATION

# MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 200 CGI BLUEEFFICIENCY 212.048 (2009-2010)



**ENGINE** M271.860  
Capacity: 5,5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Helar SP LL-03 0W-30</b>	<b>Helar SP LL-03 5W-30</b>	<b>Presteza MSP 5W-30</b>

**DIFFERENTIAL REAR**  
Capacity: 1-1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 1071</b>	<b>Gearlube LS 80W-90</b>	

**TRANSMISSION AUTOMATIC** 722.6xx 5/1  
Capacity: 8 liter

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Matic 4026</b>		

*Change every 50000 km/ 36 months*

**TRANSMISSION MANUAL** 716.6xx 6/1  
Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Gear 5015</b>		

## HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		

*Change every 24 months*

# MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 200 CGI BLUEEFFICIENCY 212.048 (2009-2010)

**POWER STEERING**

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>SP Fluid 3013</b>		

**COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 11</b>	<b>Coolant SP 12 EVO</b>	

Change every 250000 km/ 180 months

**AIRCONDITIONING COMPRESSOR**

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

**AIRCONDITIONING SYSTEM**

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*