Helar 0W-40

MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 300 4MATIC 212.080/280 (2013-2016)



•	
ENGINE M276.952 Capacity: 6,5 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	

DIFFERENTIAL FRONT Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

DIFFERENTIAL REAR 187 FE, Ø 187 mm Capacity: 0,95 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR 200 FE, Ø 200 mm Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

IMATE
oderate

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 300 4MATIC 212.080/280 (2013-2016)



2016)

TRANSMISSION AUTOMATIC 722.96x 7/1 Capacity: 9,7 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 125000 km/ 60 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 50000 km/ 36 months		

HYDRAULIC BRAKE SYSTEM Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	

COOLING SYSTEM Capacity: 9,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Change every 250000 km/ 180 months	

AIRCONDITIONING COMPRESSOR Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.