MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 350 CDI 212.025/225 (2009-



2010)

ENGINE OM642.850 Capacity: 8 liter			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30	

DIFFERENTIAL REAR Capacity: 1-1,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1071	Gearlube LS 80W-90		

TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1 Capacity: 9 liter (Dry fill)			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 2094			
Change every 50000 km/ 36 months	'		

TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1 Capacity: 9 liter (Dry fill)			
USE	CLIMATE		
Initial service	Moderate		
PRODUCT RECOMMENDATION 1			
SP Matic 4026			
Change every 50000 km/ 36 months			

TRANSMISSION MANUAL 711.670 6/1 Capacity: 1,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Gear 5015			

PRODUCT RECOMMENDATION

MERCEDES-BENZ (EU) E-CLASS W212/ V212 / S212 E 350 CDI 212.025/225 (2009-



2010)

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid-S DOT 4			
Change every 24 months	·		

POWER STEERING Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)			
use Normal		climate Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 11	Coolant SP 12 EVO		
Change avery 250000 km/ 190 mont			

Change every 250000 km/ 180 months

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.