

MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 350 CDI BLUEEFFICIENCY 212.025/225 (2009-2010)



ENGINE OM642.850
Capacity: 8 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

DIFFERENTIAL REAR
Capacity: 1-1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071	Gearlube LS 80W-90	

TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1
Capacity: 9 liter (Dry fill)

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		

Change every 50000 km/ 36 months

TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1
Capacity: 9 liter (Dry fill)

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 50000 km/ 36 months

TRANSMISSION MANUAL 711.670 6/1
Capacity: 1,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

MERCEDES-BENZ (EU) E-CLASS W212 / V212 / S212 E 350 CDI BLUEEFFICIENCY 212.025/225 (2009-2010)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 24 months*

POWER STEERING

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO*Change every 250000 km/ 180 months*

AIRCONDITIONING COMPRESSOR

Capacity: 120 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

Capacity: 590 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.