

MERCEDES-BENZ (EU) GL-CLASS X164 GL 350 CDI 4MATIC BLUEEFFICIENCY 164.822 (2010-2012)



ENGINE OM642.940
Capacity: 8,5 liter

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30

DIFFERENTIAL FRONT
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

DIFFERENTIAL REAR DIFFERENTIAL LOCK
Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

TRANSFERBOX
Capacity: 0,5 liter, Capacity: 1,5 liter (+ dual range)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

MERCEDES-BENZ (EU) GL-CLASS X164 GL 350 CDI 4MATIC BLUEEFFICIENCY 164.822 (2010-2012)


TRANSMISSION AUTOMATIC 722.9XX AS OF PRODUCTION NR. 2834527 722.9xx 7/1

Capacity: 9 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2094*Change every 125000 km/ 60 months*
TRANSMISSION AUTOMATIC 722.9XX UP TO PRODUCTION NR. 2834526 722.9xx 7/1

Capacity: 9 liter (Dry fill)

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 60000 km*
HYDRAULIC BRAKE SYSTEM ABS

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 24 months*
POWER STEERING

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032
COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO*Change every 250000 km/ 180 months*

MERCEDES-BENZ (EU) GL-CLASS X164 GL 350 CDI 4MATIC BLUEEFFICIENCY 164.822 (2010-2012)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.