

MERCEDES-BENZ (EU) GL-CLASS X164 GL

420 CDI 4MATIC 164.828 (2007-2009)



ENGINE OM629.91x
Capacity: 11,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30

PRODUCT RECOMMENDATION 3

Presteza MSP 5W-30

Change every 25000 km/ 12 months

DIFFERENTIAL FRONT

Capacity: 1,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90**DIFFERENTIAL REAR**

Capacity: 1,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Gearlube LS 80W-90**DIFFERENTIAL REAR DIFFERENTIAL LOCK**

Capacity: 1,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071**TRANSFERBOX**

Capacity: 0,5 liter, Capacity: 1,5 liter (+ dual range)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

MERCEDES-BENZ (EU) GL-CLASS X164 GL 420 CDI 4MATIC 164.828 (2007-2009)


TRANSMISSION AUTOMATIC 722.9xx 7/1

Capacity: 9 liter

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 60000 km

HYDRAULIC BRAKE SYSTEM ABS

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 24 months

POWER STEERING

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	

Change every 250000 km/ 180 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.