## MERCEDES-BENZ (EU) R-CLASS W251 R 320 CDI DPF 4MATIC 251.022/122 (2007-2009)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30

Change every 25000 km/ 12 months

DIFFERENTIAL FRONT Capacity: 1,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1071	Gearlube LS 80W-90		

DIFFERENTIAL REAR Capacity: 1,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1071	Gearlube LS 80W-90		

TRANSFERBOX Capacity: 0,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

TRANSMISSION AUTOMATIC 722.9xx 7 Capacity: 9 liter (Dry fill)	
USE	CLIMATE
First change only	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Change every 60000 km	

## MERCEDES-BENZ (EU) R-CLASS W251 R 320 CDI DPF 4MATIC 251.022/122 (2007-2009)



HYDRAULIC BRAKE SYSTEM ABS Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	·

POWER STEERING Capacity: 1,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4026	SP Matic 2032		

COOLING SYSTEM Capacity: 10,1-13 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	
Change every 250000 km/ 180 mod	nths	

## **AIRCONDITIONING COMPRESSOR**

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 970 grams, Capacity: 1220 grams (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.