ENCINE MOZE OF

# MERCEDES-BENZ (EU) R-CLASS W251 R 350 4MATIC 251.057/157 (2011-2013)



USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Helar 0W-40	
Change every 25000 km	
DIFFERENTIAL FRONT Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	
DIFFERENTIAL REAR	
Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

TRANSFERBOX Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	

TRANSMISSION AUTOMATIC 722.906 7 Capacity: 9 liter (Dry fill)	1	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 125000 km/ 60 months		

## MERCEDES-BENZ (EU) R-CLASS W251 R 350 4MATIC 251.057/157 (2011-2013)



HYDRAULIC BRAKE SYSTEM ABS Capacity: 0,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	

ELECTRO-HYDRAULIC POWER S Capacity: 1,5 liter	STEERING (EHPS)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4026	SP Matic 2032		

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
SP Matic 2032		
		PRODUCT RECOMMENDATION 2

COOLING SYSTEM Capacity: 9,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 11	Coolant SP 12 EVO	
Change every 250000 km/ 180 mo	nths	'

## **AIRCONDITIONING COMPRESSOR**

We are unable to give a standard recommendation for this component. Please contact our service department.

## **AIRCONDITIONING SYSTEM**

Capacity: 970 grams, Capacity: 1220 grams (with 2 zone airconditioning system)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.