## MERCEDES-BENZ (EU) S-CLASS W222 / V222 / X222 S 350 BLUETEC 222.032/132



(2013-2015)

ENGINE OM642.861 Capacity: 8 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Presteza MSP 5W-30
	•	:

Change every 25000 km

<b>DIFFERENTIAL REAR</b> 200 FE, Ø 200 Capacity: 1,1 liter	mm	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1071		

<b>DIFFERENTIAL REAR</b> 215 FE, Ø 215 mr Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

FE, Ø 240 mr	
	ATE .
	erate

TRANSMISSION AUTOMATIC 722.9xx 7 Capacity: 9 liter (Dry fill)	1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2094		
Change every 125000 km/ 60 months		

PRODUCT RECOMMENDATION

## MERCEDES-BENZ (EU) S-CLASS W222 / V222 / X222 S 350 BLUETEC 222.032/132



(2013-2015)

ACTIVE BODY CONTROL SYSTEM Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

HYDRAULIC BRAKE SYSTEM ABS Capacity: 0,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Change every 24 months	'

COOLING SYSTEM Capacity: 11,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Change every 200000 km/ 120 months	'

## AIRCONDITIONING COMPRESSOR

Capacity: 110 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 660 grams, Capacity: 770 grams (+ code 582)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.